



MPR Kirschner Wires/Steinmann Pins



Description

Stainless steel wires used to repair fractures by holding broken bones together. Known as Kirschner Wires or K-Wires under 2mm in diameter, and Steinmann Pins 2mm and up.

MPR Orthopedics offers a wide variety of threaded and unthreaded Kirschner Wires & Steinmann Pins, in a range of lengths, point types, and diameters. Threaded wires/pins resist being shifted or pulled before the fracture has healed, while unthreaded wires/pins offer a high degree of ease of application and removal.

Product Specifications

See pages 2–3 for information on Kirschner Wires, and page 4 for information on Steinmann Pins.

For Further Information

If further information on these products is required, please contact MPR Orthopedics Customer Service at 800.524.5194 in the United States, or your authorized representative, or visit the MPR Orthopedics website at www.mprortho.com.

MPR Kirschner Wires, 4"

NON-THREADED

#	POINT(S)	DIAMETER
186-04-28	Single Trocar	0.028" (0.7mm)
186-04-35	Single Trocar	0.035" (0.9mm)
186-04-45	Single Trocar	0.045" (1.1mm)
186-04-54	Single Trocar	0.054" (1.4mm)
186-04-62	Single Trocar	0.062" (1.6mm)
1642-00	Double Trocar	0.028" (0.7mm)
1643-10	Double Trocar	0.035" (0.9mm)
1644-10	Double Trocar	0.045" (1.1mm)
1645-10	Double Trocar	0.054" (1.4mm)
1646-10	Double Trocar	0.062" (1.6mm)
186-54	Double Diamond	0.035" (0.9mm)
186-70	Double Diamond	0.045" (1.1mm)
186-86	Double Diamond	0.062" (1.6mm)

MPR Kirschner Wires, 5⁷/₈"

NON-THREADED

#	POINT(S)	DIAMETER
186-91	Single Trocar	0.035" (0.9mm)
186-93	Single Trocar	0.062" (1.6mm)

MPR Kirschner Wires, 6"

NON-THREADED

#	POINT(S)	DIAMETER
186-06-28	Single Trocar	0.028" (0.7mm)
186-06-35	Single Trocar	0.035" (0.9mm)
186-06-45	Single Trocar	0.045" (1.1mm)
186-06-54	Single Trocar	0.054" (1.4mm)
186-06-62	Single Trocar	0.062" (1.6mm)
186-43	Double Trocar	0.028" (0.7mm)
186-44	Double Trocar	0.035" (0.9mm)
186-60	Double Trocar	0.045" (1.1mm)
186-06-19	Double Trocar	0.054" (1.4mm)
186-76	Double Trocar	0.062" (1.6mm)
186-74	Double Diamond	0.045" (1.1mm)

THREADED

#	POINT(S)	DIAMETER
186-60T	Double Trocar	0.045" (1.1mm)
186-76T	Double Trocar	0.062" (1.6mm)

MPR Kirschner Wires, 9"

NON-THREADED

#	POINT(S)	DIAMETER
186-50	Single Trocar	0.035" (0.9mm)
186-66	Single Trocar	0.045" (1.1mm)
186-82	Single Trocar	0.062" (1.6mm)
186-46	Double Trocar	0.035" (0.9mm)
186-62	Double Trocar	0.045" (1.1mm)
186-73	Double Trocar	0.054" (1.4mm)
186-78	Double Trocar	0.062" (1.6mm)
186-01-69	Single Diamond	0.035" (0.9mm)
186-02-69	Single Diamond	0.045" (1.1mm)
186-03-69	Single Diamond	0.062" (1.6mm)
186-00-79	Double Diamond	0.028" (0.7mm)
186-01-79	Double Diamond	0.035" (0.9mm)

#	POINT(S)	DIAMETER
186-02-79	Double Diamond	0.045" (1.1mm)
186-03-79	Double Diamond	0.062" (1.6mm)

THREADED

#	POINT(S)	DIAMETER
2620-05	Single Trocar	0.062" (1.6mm)
2620-39	Double Trocar	0.035" (0.9mm)
2620-37	Double Trocar	0.045" (1.1mm)
2620-35	Double Trocar	0.062" (1.6mm)
262-11	Double Diamond	0.035" (0.9mm)
262-12	Double Diamond	0.045" (1.1mm)
262-13	Double Diamond	0.062" (1.6mm)

MPR Steinmann Pins, 9"

NON-THREADED

#	POINT(S)	DIAMETER
187-01-59	Single Trocar	0.079" (2.0mm)
187-02-59	Single Trocar	0.094" (2.4mm)
187-03-59	Single Trocar	0.110" (2.8mm)
187-04-39	Single Trocar*	0.125" (3.2mm)
187-04-59	Single Trocar	0.125" (3.2mm)
187-05-59	Single Trocar	0.142" (3.6mm)
187-06-59	Single Trocar	0.157" (4.0mm)
187-07-59	Single Trocar	0.189" (4.8mm)
187-01-19	Double Trocar	0.079" (2.0mm)
187-02-19	Double Trocar	0.094" (2.4mm)
187-03-19	Double Trocar	0.110" (2.8mm)
187-04-19	Double Trocar	0.125" (3.2mm)
187-05-19	Double Trocar	0.142" (3.6mm)
187-06-19	Double Trocar	0.157" (4.0mm)
187-07-19	Double Trocar	0.189" (4.8mm)
187-01-49	Single Diamond*	0.079" (2.0mm)
187-01-69	Single Diamond	0.079" (2.0mm)
187-02-49	Single Diamond*	0.094" (2.4mm)
187-02-69	Single Diamond	0.094" (2.4mm)
187-03-69	Single Diamond	0.110" (2.8mm)
187-04-49	Single Diamond*	0.125" (3.2mm)
187-04-69	Single Diamond	0.125" (3.2mm)
187-05-69	Single Diamond	0.142" (3.6mm)
187-06-69	Single Diamond	0.157" (4.0mm)
187-07-69	Single Diamond	0.189" (4.8mm)
187-01-79	Double Diamond	0.079" (2.0mm)
187-02-79	Double Diamond	0.094" (2.4mm)
187-03-79	Double Diamond	0.110" (2.8mm)
187-04-79	Double Diamond	0.125" (3.2mm)

#	POINT(S)	DIAMETER
187-05-79	Double Diamond	0.142" (3.6mm)
187-06-79	Double Diamond	0.157" (4.0mm)
187-07-79	Double Diamond	0.189" (4.8mm)

THREADED

#	POINT(S)	DIAMETER
2620-33	Single Trocar	0.079" (2.0mm)
2620-29	Single Trocar	0.094" (2.4mm)
2620-25	Single Trocar	0.110" (2.8mm)
2620-23	Single Trocar	0.125" (3.2mm)
2620-19	Single Trocar	0.142" (3.6mm)
2620-17	Single Trocar	0.157" (4.0mm)
2620-13	Single Trocar	0.189" (4.8mm)
262-05-04	Single Diamond	0.110" (2.8mm)
262-03-04	Single Diamond	0.142" (3.6mm)
262-02-04	Single Diamond	0.157" (4.0mm)

*3-sided shank one end